

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

**(19) World Intellectual Property Organization
International Bureau**



(43) International Publication Date
7 April 2005 (07.04.2005)

PCT

(10) International Publication Number
WO 2005/031075 A1

(51) International Patent Classification⁷:
E03D 1/32, F16K 31/30

E03C 1/10,

(72) Inventor; and

(75) Inventor/Applicant (for US only): SMITH, John, William [AU/AU]; 34 Alden Court, Cheltenham, VIC 3192 (AU).

(21) International Application Number:

PCT/AU2004/001304

(74) Agent: GRIFFITH HACK; Level 3, 509 St Kilda Road, Melbourne, VIC 3004 (AU).

(22) International Filing Date:

24 September 2004 (24.09.2004)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:


Priority Data: 26 September 2003 (26.09.2003) All

(71) *Applicant (for all designated States except US): SENSEI TRADING PROPRIETARY LIMITED [AU/AU]; 35A Broomfield Road, Hawthorn East, VIC 3123 (AU).*

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: ADJUSTABLE INLET VALVE WITH AIR GAP



(57) Abstract: A valve arrangement for use in the cistern (8) of a toilet is described having an inlet valve (20) operated by a float (46) such that when the level of water in the cistern reaches a threshold amount, the float operates the inlet valve to substantially instantaneously close the supply of incoming water. The inlet valve of the valve arrangement is provided with an air gap or clearance (51) to eliminate, prevent or reduce siphoning of water from the cistern into the water supply when the valve is in the fully closed position. The air gap allows water within the inlet valve to drain into the cistern so as to form the air gap.

WO 2005/031075 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.